

# Safety Data Sheet

According to Australia Model Code of Practice for the preparation of  
Safety Data Sheets for Hazardous Chemicals (GHS)



## SECTION 1: Identification

<b>Product Identifier</b>	<b>Super-D EC® Diesel Engine Oil</b>
<b>Code</b>	<b>LBKN830033</b>
<b>Other means of identification</b>	Kendall Super-D EC Diesel Engine Oil SAE 10W-30, CK-4 Kendall Super-D EC Diesel Engine Oil SAE 15W-40, CK-4
<b>Recommended use of the chemical and restrictions on use</b>	
<b>Recommended use</b>	Heavy Duty Diesel Engine Oil
<b>Restrictions on use</b>	All others
<b>24 Hour Emergency Phone Number</b>	CHEMTREC Australia +612 9037 2994 CHEMTREC Global +011 703 527 3887

### Details of manufacturer or importer

#### Manufacturer/Supplier

Phillips 66 Lubricants  
P.O. Box 4428  
Houston, TX 77210

#### SDS Information

URL: [www.Phillips66.com/SDS](http://www.Phillips66.com/SDS)  
Phone: 800-762-0942  
Email: [SDS@P66.com](mailto:SDS@P66.com)

#### Customer Service

Australia: 1300 744 554

#### Australian Importer

Oil & Energy Pty Ltd  
20 Ambitious Link  
Bibra Lake WA 6163

#### Australian Importer

Pacific Petroleum Products  
1628 Ipswich Rd  
Rocklea QLD 4106

## SECTION 2: Hazard identification

### Classified Hazards

Not classified as a hazardous substance in accordance with the criteria of Safe  
Work Australia - Globally Harmonised System (GHS)

### Other hazards which do not result in classification

PHNOC: None known

HHNOC: None known

### Label elements, including precautionary statements

No classified hazards

## SECTION 3: Composition/information on ingredients

### Mixture

<b>Chemical Name</b>	<b>CASRN</b>	<b>Concentration</b>
Distillates, petroleum, hydrotreated heavy paraffinic	64742-54-7	<80
Lubricant Base Oil (Petroleum)	VARIOUS	<15
Other components not contributing to product hazard(s)	VARIOUS	<15

<sup>1</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## SECTION 4: First aid measures

### Description of necessary first aid measures

**Eye Contact:** If irritation or redness develops from exposure, flush eyes with clean water. If symptoms persist, seek medical attention.

**Skin Contact:** Remove contaminated shoes and clothing and cleanse affected area(s) thoroughly by washing with mild soap and water or a waterless hand cleaner. If irritation or redness develops and persists, seek medical attention.

**Inhalation:** First aid is not normally required. If breathing difficulties develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. Seek immediate medical attention.

**Ingestion:** First aid is not normally required; however, if swallowed and symptoms develop, seek medical attention.

**Symptoms caused by exposure:** Prolonged or repeated contact may dry skin and cause irritation. Inhalation of oil mists or vapours generated at elevated temperatures may cause respiratory irritation. Accidental ingestion can result in minor irritation of the digestive tract, nausea and diarrhea.

**Medical attention and special treatment:** Acute aspirations of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

## SECTION 5: Firefighting measures

**Suitable extinguishing equipment:** Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F / 100°C. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

### Specific hazards arising from the chemical

**Unusual Fire & Explosion Hazards:** This material may burn, but will not ignite readily. If container is not properly cooled, it can rupture in the heat of a fire.

**Hazardous Combustion Products:** Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of sulphur, nitrogen or phosphorus may also be formed.

**Special protective equipment and precautions for fire fighters:** For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapours and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

**Hazchem code:** None

See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits

## SECTION 6: Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** This material may burn, but will not ignite readily. Keep all sources of ignition away from spill/release. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorised personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

**Environmental Precautions:** Stop and contain spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorised drainage systems, and natural waterways. Use water sparingly to minimize environmental contamination and reduce disposal requirements. If spill occurs on water notify appropriate authorities and advise shipping of any hazard. Spills into or upon navigable waters, the contiguous zone, or adjoining shorelines that cause a sheen or discoloration on the surface of the water, may require notification.

**Methods and material for containment and cleaning up:** Notify relevant authorities in accordance with all applicable regulations. Immediate cleanup of any spill is recommended. Dike far ahead of spill for later recovery or disposal. Absorb spill with inert material such as sand or vermiculite, and place in suitable container for disposal. If spilled on water remove with appropriate methods (e.g. skimming, booms or absorbents). In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken. See Section 13 for information on appropriate

disposal.

**SECTION 7: Handling and storage**

**Precautions for safe handling:** Keep away from flames and hot surfaces. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8). Spills will produce very slippery surfaces. Used motor oils have been shown to cause skin cancer in mice after repeated application to the skin without washing. Brief or intermittent skin contact with used motor oil is not expected to cause harm if the oil is thoroughly removed by washing with soap and water. Do not enter confined spaces such as tanks or pits without following proper entry procedures. Do not wear contaminated clothing or shoes.

**Conditions for safe storage, including any compatibilities:** Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well-ventilated area away from heat and all sources of ignition. Store only in approved containers. Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Before working on or in tanks which contain or have contained this material, refer to appropriate guidance pertaining to cleaning, repairing, welding, or other contemplated operations.

**SECTION 8: Exposure controls/personal protection**

**Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.**

Exposure control measures			
Chemical Name	Australia (HCIS)	ACGIH	Phillips 66
Distillates, petroleum, hydrotreated heavy paraffinic	None	TWA-8hr: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup> as Oil Mist, if Generated	None
Lubricant Base Oil (Petroleum)	None	TWA-8hr: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup> as Oil Mist, if Generated	None

**Biological Limit Values**

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

**Engineering controls:** If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

**Eye/Face Protection:** The use of eye protection that meets or exceeds EN 166 is recommended to protect against potential eye contact, irritation, or injury. Depending on conditions of use, close fitting eye protection and a face shield may be necessary.

**Skin/Hand Protection:** The use of gloves impervious to the specific material handled that comply with EN 374 is advised to prevent skin contact. Users should check with manufacturers to confirm the breakthrough performance of their products. Suggested protective materials: Nitrile rubber. Wear thermal insulating gloves and face shield or eye protection when working with materials that present thermal hazards (hot or cold).

**Respiratory Protection:** A respiratory protection programme that follows recommendations for the selection, use, care and maintenance of respiratory protective devices in EN 529:2005 should be followed whenever workplace conditions warrant a respirator's use. Where there is potential for airborne exposure above the exposure limit an approved air purifying respirator equipped with Type A, organic gases and vapours filter (as specified by the manufacturer) in combination with Type P2 - Medium efficiency particle filters may be used. Air purifying respirators provide limited protection and cannot be used in atmospheres that exceed the maximum use concentration (as directed by regulation or the manufacturer's instructions), in oxygen deficient (less than 19.5 percent oxygen) situations, or under conditions that are immediately dangerous to life and health.

**Environmental Exposure Controls:** Refer to Sections 6, 7, 12 and 13.

**Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.**

**SECTION 9: Physical and chemical properties**

<b>Appearance:</b>	Amber, Transparent
<b>Physical Form:</b>	Liquid
<b>Odour:</b>	Petroleum
<b>Odour Threshold:</b>	Not determined
<b>pH</b>	Not applicable
<b>Melting/Freezing Point:</b>	Not determined
<b>Initial Boiling Point/Range:</b>	Not determined
<b>Flash Point:</b>	220 °C; (ASTM D93)
<b>Evaporation Rate (nBuAc=1):</b>	Not determined
<b>Flammability (solid, gas):</b>	Not applicable
<b>Upper Explosive Limits (vol % in air):</b>	Not determined
<b>Lower Explosive Limits (vol % in air):</b>	Not determined
<b>Vapour Pressure:</b>	Not determined
<b>Vapour Density</b>	>1
<b>Relative Density (water=1):</b>	0.87 - 0.88 @ 15.6°C
<b>Solubility (ies):</b>	Solubility in water: Negligible
<b>Partition Coefficient (n-octanol/water) (Kow):</b>	Not determined
<b>Auto-ignition Temperature:</b>	Not determined
<b>Decomposition Temperature:</b>	Not determined
<b>Viscosity:</b>	12.0 - 15.3 cSt @ 100°C; 82 - 119 cSt @ 40°C

Other physical or chemical parameters relevant to health and safety

<b>Pour Point:</b>	-33 °C
<b>Bulk Density:</b>	7.25 - 7.32 lbs/gal

**SECTION 10: Stability and reactivity**

**Reactivity:** Not chemically reactive.

**Chemical stability:** Stable under normal ambient and anticipated conditions of use.

**Possibility of hazardous reactions:** Hazardous reactions not anticipated.

**Conditions to avoid:** Extended exposure to high temperatures can cause decomposition. Avoid all possible sources of ignition.

**Incompatible materials:** Avoid contact with strong oxidizing agents and strong reducing agents.

**Hazardous decomposition products:** Not anticipated under normal conditions of use, During use in engines, contamination of oil with low levels of hazardous fuel combustion by-products (e.g. polycyclic aromatic hydrocarbons) may occur.

**SECTION 11: Toxicological information**

Information on Toxicological Effects

Substance / Mixture			
Acute Toxicity	Hazard	Additional Information	LC50/LD50 Data
Inhalation	Unlikely to be harmful		>5 mg/L (mist, estimated)
Dermal	Unlikely to be harmful		> 2 g/kg (estimated)
Oral	Unlikely to be harmful		> 5 g/kg (estimated)

**Likely Routes of Exposure:** Inhalation, eye contact, skin contact

**Skin Corrosion/Irritation:** Causes mild skin irritation. Repeated exposure may cause skin dryness or cracking.

**Serious Eye Damage/Irritation:** Causes mild eye irritation.

**Skin Sensitisation:** No information available on the mixture, however none of the components have been classified for skin sensitisation (or are below the concentration threshold for classification).

**Respiratory Sensitisation:** No information available.

**Germ Cell Mutagenicity:** No information available on the mixture, however none of the components have been classified for germ cell mutagenicity (or are below the concentration threshold for classification).

**Carcinogenicity:** No information available on the mixture, however none of the components have been classified for carcinogenicity (or are below the concentration threshold for classification).

**Reproductive Toxicity:** No information available on the mixture, however none of the components have been classified for reproductive toxicity (or are below the concentration threshold for classification).

**Specific Target Organ Toxicity (Single Exposure):** No information available on the mixture, however none of the components have been classified for target organ toxicity (or are below the concentration threshold for classification).

**Specific Target Organ Toxicity (Repeated Exposure):** No information available on the mixture, however none of the components have been classified for target organ toxicity (or are below the concentration threshold for classification).

**Aspiration Hazard** Not expected to be an aspiration hazard

#### Information on Toxicological Effects of Components

##### Lubricant Base Oil (Petroleum)

*Carcinogenicity:* The petroleum base oils contained in this product have been highly refined by a variety of processes including severe hydrocracking/hydroprocessing to reduce aromatics and improve performance characteristics. All of the oils meet the IP-346 criteria of less than 3 percent PAH's and are not considered carcinogens by NTP, IARC, or OSHA.

## SECTION 12: Ecological information

**Ecotoxicity:** All acute aquatic toxicity studies on samples of lubricant base oils show acute toxicity values greater than 100 mg/L for invertebrates, algae and fish. These tests were carried out on water accommodated fractions and the results are consistent with the predicted aquatic toxicity of these substances based on their hydrocarbon compositions.

**Persistence and Degradability:** The hydrocarbons in this material are not readily biodegradable, but since they can be degraded by microorganisms, they are regarded as inherently biodegradable.

**Bioaccumulative Potential:** Log Kow values measured for the hydrocarbon components of this material are greater than 5.3, and therefore regarded as having the potential to bioaccumulate. In practise, metabolic processes may reduce bioconcentration.

**Mobility in Soil:** Volatilisation to air is not expected to be a significant fate process due to the low vapour pressure of this material. In water, base oils will float and spread over the surface at a rate dependent upon viscosity. There will be significant removal of hydrocarbons from the water by sediment adsorption. In soil and sediment, hydrocarbon components will show low mobility with adsorption to sediments being the predominant physical process. The main fate process is expected to be slow biodegradation of the hydrocarbon constituents in soil and sediment.

**Other adverse effects:** None anticipated.

## SECTION 13: Disposal considerations

**Disposal Recommendations:** This material under most intended uses would become "waste oils" due to contamination by physical or chemical impurities. Whenever possible, recycle "waste oils" in accordance with current national and regional provisions.

**Empty Containers:** Container contents should be completely used and containers emptied prior to discard. Empty drums should be properly sealed and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with applicable regulations.

## SECTION 14: Transport information

**UN Number:** Not regulated

**UN proper shipping name:** None

**Transport hazard class(es):** None

Packing Group: None

Environmental Hazards: This product does not meet the ADG/UN/IMDG/IMO criteria of a marine pollutant

Special precautions for user: None

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Hazchem code: None

## SECTION 15: Regulatory information

### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

No Poisons Schedule number allocated.

### National Pollutant Inventory (NPI)

Chemical Name	National Pollutant Inventory (NPI)
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and isopropyl) esters, zinc salts	10 tonne/yr Threshold category 1

### The Montreal Protocol on Substances that Deplete the Ozone Layer

Not applicable

### The Stockholm Convention on Persistent Organic Pollutants

Not applicable

### The Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade

Not applicable

### Control of Transboundary Movements of Hazardous Wastes and their Disposal (Basel Convention)

Not applicable

### Inventory Status:

One or more components of this product are not listed on AICS.

## SECTION 16: Other information

Issue Date:	Previous Issue Date:	SDS Number	Status:
16-Apr-2018	None	LBKN830033	FINAL

### Revised Sections or Basis for Revision:

New SDS

### Guide to Abbreviations:

ACGIH = American Conference of Governmental Industrial Hygienists; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling Limit (15 minutes); GHS = Globally Harmonized System; HCIS = Hazardous Chemical Information System; IARC = International Agency for Research on Cancer; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; NE = Not Established; NTP = National Toxicology Program; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit Value (ACGIH); TWA = Time Weighted Average (8 hours); UEL = Upper Explosive Limit;

### Disclaimer of Expressed and implied Warranties:

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to

adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorisation is given nor implied to practice any patented invention without a licence.